



The Pik Rite Hydra-Pull 1880 VB



Built to Work the Way You Work

- Pik Rite's latest addition to our line of Manure Handling Equipment
- Developed to meet the demands of larger farm operators and custom haulers
- Shreds packed manure and spreads in wide pattern

"It's the best thing since the invention of the pitchfork."





Features and Options:

- Vertical Beaters provide a wide and consistent spread pattern.
- 27,500# axles w/ heavy-duty lubricated wheel bearings.
- 700/40-22.5 tires for better floatation and high weight capacity.
- 10,000# side wind jack with safety chain is standard.
- Vertically adjustable articulating implement hitch with greasable ball and socket for smooth operation. (max pull exceeds 180,000#)
- All bearings have easy access grease fitting banks.
- Air drum brakes for consistent stopping power and longer life, compared to disk brakes.
- Tapered sides with set-in wheels allow for easier loading.
- Hydraulic driven hook and eye apron chain handles large loads with ease.
- Unloading speed from 0 to 16ft per minute.
- Hydraulic endgate contains free flowing material.
- 3/8" rubber protection flap hangs from endgate to protect tractor and operator.
- Road safety and field work lights standard.
- Available in green or industrial yellow.

Capacity	880 Bushels
Struck level ASAE S324.1	712 cu. Ft.
Heaped ASAE S324.1	1096 cu. Ft.
Load carrying capacity	24.2 tons
Inside width of box	60 in. to 96 in.
Depth of box	53.2 in.
Overall width w/floatation tires / tire size	132 in./ 700/40-22.5
Overall height	120 in.
Overall length	31ft. 6in.
Bed Length	24 ft.
Number of beaters	2
Beater speed	420 rpm
Fan diameter	34.6 in.
Number of paddles on beaters	70 total
Tractor PTO horsepower min. recommended	200 hp
Number of unloading speeds	Infinite from 0 - 16 ft./min.
PTO speed	1000
PTO shaft diameter	1-3/4 in.
Number of endgate cylinders	2
Tare weight	17040#
Load height	93.2 in

Pik Rite Inc. 60 Pik Rite Lane, Lewisburg PA 17837

570-523-8174 Fax: 570-523-8175