

INTRODUCING A BRAND NEW MODEL

**pikrite** HP **500**



**Hydra-Pull**  
SPREADERS

- **500** BUSHEL CAPACITY
- HEAVY DUTY PINTLE CHAIN
- DIRECT DRIVE BEATER SYSTEM
- METERING GUILLOTINE ENDGATE
- WEIGH SCALE INSTALLATION READY
- FLARED SIDES WITH OPTIONAL SIDE EXTENSIONS
- CLUTCH PROTECTED DRIVELINES (SLIP/OVER-RUN)
- QUICK DETACH BEATERS  
(INTERCHANGEABLE FOR COMPOST OR VERTICAL BEATERS)



**PROUDLY MADE IN THE USA**







**BUILT TO WORK THE WAY YOU WORK**

### Efficient

- VERTICAL BEATERS PROVIDE A WIDE AND CONSISTENT SPREAD PATTERN
- HYDRAULIC METERING END GATE CONTAINS FREE FLOWING MATERIAL
- ADJUSTABLE APRON SPEED (0-16 FT. PER MIN.)

### Durable

- HEAVY DUTY WALKING BEAMS
- 10,000 LB. SIDE WIND JACK W/ SAFETY CHAIN
- WH124 PINTLE CHAIN RATED UP TO 60,000 LBS
- SPRING LOADED TAKE-UP BEARINGS ALLOW FOR CHAIN FLEX WITHOUT DAMAGE

### Operator Friendly

- ALL BEARINGS HAVE EASY ACCESS GREASE FITTING BANKS
- SLOPED SIDES ALLOW FOR EASIER LOADING
- ROAD SAFETY AND FIELD WORK LIGHTS
- AVAILABLE IN TRADITIONAL GREEN, INDUSTRIAL YELLOW, RED OR BLUE



Capacity	500 BUSHEL
Struck Level ASAE S324.1	425 CUBIC FT.
Heaped ASAE S324.1	622 CUBIC FT.
Load carrying capacity	16.6 TONS
Inside width of box	83.5 IN. - 65 IN.
Depth of box	47.2 IN.
Overall width w/flotation tires (tire size)	118.25 IN. (550/60-22.5 RADIAL TIRES)
Overall height (gate closed)	118 IN.
Loading height	89 IN.
Overall length	27 FT. 4 IN.
Bed length	218 IN.
Number of beaters	2
Beater speed	420 RPM.
Fan diameter	34.6 IN.
Number of paddles on beaters	70 TOTAL
Tractor PTO hp min. recommended	150 HP.
Number of unloading speeds	INFINITE FROM 0-15.21 FT./MIN.
PTO speed	1000
PTO shaft diameter	1 3/4 IN.
Number of end gate cylinders	2

60 Pik Rite Lane Lewisburg, PA 17837 (570) 523-8174

For more information: Call: 1-800-326-9763 Email: sales@pikrite.com www.pikrite.com

**PROUDLY MADE IN THE USA**

